

MAIN FEATURES :

UNDERHUNG MOTOR DESIGN

55 MM TITANIUM VC FORMER

SOFT RUBBER SURROUND

VENTED VC, POLE PIECE & SPIDER

32 HZ - 2 KHZ IN VENTED BOX

The C220 – 6 – 222 is an 8 inch bass driver with ultra hard ceramic dome.

A FEA optimized overhung motor design with 55 mm titanium voice coil former guarantees very low energy storage and good heat transfer. Its high force factor leads to outstanding transient response for more realistic reproduction.

The low loss rubber surround and a thin fabric spider center the moving parts with high linearity.

The recommended application for this excellent bass driver is from 32 Hz - 2000 Hz



Mechanical data

Overall diameter	220	
Cutout hole diameter	190.5	
Frontplate depth		
Overall depth	107	
Motor assembly diameter	120	
Motor assembly depth	44	
Screw fitting	DIN 7984, 4mm	
Terminal	+:6.3 x 0.8 / -: 4.8 x 0.8	
Shipping weight / net weight	4.1 / 3.8	
Shipping box size	250 / 145 / 250	

Thiele/Small Parameters

Sensitivity (2.83V / 1m)	Lp	93*	
DC-resistance	Re		Ohm
Resonance frequency	Fs	24	Hz
Equivalent volume of air		115	
Mechanical Q	Qms	4.4	
Electrical Q	Qes	0.20	
Total Q	Qts	0.19	
Effective piston area	Sd	224	
Moving mass	Mms	27	
Suspension compliance	Cms		mm/N
Mechanical resistance	Rms	0.89	kg x s

Voice Coil data

Power handling		150*	Watt
Linear excursion	Xmax		
Voice coil diameter			
Voice coil former material			
Voice coil material		Cu	
Voice coil inductance	Le	0.42	mΗ
Force factor		11.5	N/A
Motor type		Underhung	
Ferrofluid filling			