

C173-6-096E

Bass - midrange driver

DOMEMATERIAL:	CERAMIC
APPLICATION:	BASS - MIDRANGE
NOMINAL DIAMETER:	173 mm
SENSITIVITY:	92.5 dB



MAIN FEATURES :

SPECIAL DOME CUTOUTS

UNDERHUNG MOTOR DESIGN

55 MM TITANIUM VC FORMER

SOFT RUBBER SURROUND

VENTED VC, POLE PIECE & SPIDER

40 HZ - 3 KHZ IN VENTED BOX

The **C173 – 6 – 096E** is a 6.5 inch bass-midrange driver with ultra hard **ceramic dome**.

Anti - resonant **cutout fills** in the ceramic dome provide for damping of the 6 kHz dome resonance.

A **FEA optimized** underhung motor design with 55 mm titanium voice coil former guarantees very low energy storage and good heat transfer. Its **high force factor** leads to outstanding transient response for more realistic reproduction.


The low loss rubber surround and a **thin fabric spider** center the moving parts with high linearity.

For this amazing bass-midrange driver, we recommend an application from 40 Hz – 3000 Hz.

6 HOLES $\varnothing 4.5$ AT $\varnothing 161.80$



C173-6-096E



Mechanical data

Overall diameter
Cutout diameter
Frontplate depth
Overall depth
Motor assembly diameter
Motor assembly depth
Screw fitting
Terminal
Shipping weight / net weight
Shipping size

	173	mm
	145.6	mm
	6.35	mm
	96.35	mm
	120	mm
	44	mm
	DIN 7984, 4mm	
	+ : 6.3 x 0.8 / - : 4.8 x 0.8	mm
	3.76 / 3.44	kg
	210 / 140 / 210	mm

Thiele/Small Parameters

Sensitivity (2.83V / 1m)
DC-resistance
Resonance frequency
Equivalent volume of air
Mechanical Q
Electrical Q
Total Q
Effective piston area
Moving mass
Suspension compliance
Mechanical resistance

Lp	92.5*	dB
Re	6.61	Ohm
Fs	36	Hz
Vas	29.8	L
Qms	4.07	
Qes	0.18	
Qts	0.22	
Sd	130	cm ²
Mms	15.5	g
Cms	1.23	mm/N
Rms	0.87	kg x s

Voice Coil data

Power handling
Linear excursion
Voice coil diameter
Voice coil former material
Voice coil material
Voice coil inductance
Force factor
Motor type
Ferrofluid filling

P	120*	Watt
Xmax	+/- 5	mm
	55	mm
	Ti	
	Cu	
Le	0.20	mH
Bl	11.5	N/A
	Underhung	
	no	

* Please refer to www.accuton.com for exact measurement conditions and further information.

All rights reserved - All data with reservation and subject to change.

Thiel & Partner GmbH Kantstrasse 1 50259 Pulheim T +49 (0) 2238 / 475475 a.bankewitz@accuton.com