

MAIN FEATURES :

UNDERHUNG MOTOR DESIGN

55 MM TITANIUM VC FORMER

SOFT RUBBER SURROUND

VENTED VC, POLE PIECE & SPIDER

31 HZ - 1 KHZ IN VENTED BOX

The **S220** – **6** – **222** is an 8 inch bass driver with ultra stiff ceramic - sandwich dome.

A FEA optimized overhung motor design with 55 mm titanium voice coil former guarantees very low energy storage and good heat transfer. Its high force factor leads to outstanding transient response for more realistic reproduction.

The low loss rubber surround and a **thin fabric spider** center the moving parts with high linearity.

The recommended application for this excellent bass driver is from 31 Hz - 1000 Hz

| nical data | | | |
|------------------------------|-----------------------------|----|--|
| Overall diameter | 220 | mm | |
| Cutout hole diameter | 190.5 | mm | |
| Frontplate depth | 9 | mm | |
| Overall depth | 107 | mm | |
| Motor assembly diameter | 120 | mm | |
| Motor assembly depth | 44 | mm | |
| Screw fitting | DIN 7984, 4mm | | |
| Terminal | +: 6.3 x 0.8 / -: 4.8 x 0.8 | mm | |
| Shipping weight / net weight | 4.1 / 3.8 | kg | |
| Shipping box size | 250 / 145 / 250 | mm | |

| Small Parameters | | | |
|--------------------------|-----|-------|--------|
| Sensitivity (2.83V / 1m) | Lp | 92.5* | dB |
| DC-resistance | Re | 6.7 | Ohm |
| Resonance frequency | Fs | 21 | Hz |
| Equivalent volume of air | Vas | 139 | L |
| Mechanical Q | Qms | 4.4 | |
| Electrical Q | Qes | 0.21 | |
| Total Q | Qts | 0.20 | |
| Effective piston area | Sd | 224 | cm² |
| Moving mass | Mms | 30 | g |
| Suspension compliance | Cms | 1.95 | mm/N |
| Mechanical resistance | Rms | 0.89 | kg x s |

| Coil data | | | |
|----------------------------|------|-----------|------|
| Power handling | Р | 150* | Watt |
| Linear excursion | Xmax | +/- 5 | mm |
| Voice coil diameter | | 55 | mm |
| Voice coil former material | | Ti | |
| Voice coil material | | Cu | |
| Voice coil inductance | Le | 0.42 | mH |
| Force factor | ВІ | 11.5 | N/A |
| Motor type | | Underhung | |
| Ferrofluid filling | | no | |

^{*} Please refer to www.accuton.com for exact measurement conditions and further information.